Contempo 54mm Rebated Aluminium Framed Door

Double Glazed - Specification Overview

FusionPartitions

Document No. FP-NBS.6

Framing Dimensions:

Face bonded safety glass with a 63mm back painted border covering the 63mm x 54mm aluminium perimeter frame with a 9mm x 15mm rebate.

Acoustics Performance:

55mm thick rebated door with 2 x 6mm toughened safety glass, drop down threshold and full perimeter seals - Rw 41dB.
55mm thick rebated Type '54S' door, drop down threshold and full perimeter seals - Rw 46dB.

Integration:

The door will fully integrated with all Fusion glazed partitioning systems and both the 75mm and 100mm plasterboard partition wall systems.

Colour Finish:

Polyester powder coated in any BS4800 or RAL colours available to order.
A selection of anodised and other special finishes are also available to order.

Manifestation:

To meet the requirements of Part M of the Building Regulations (*minimum 50mm dots @ 100mm centres*) or to clients specification using Digital printed logos / graphics on film, screen printed or acid etched glass.

Door Frames:

A range of acoustic performance enhancing single or double glazed aluminium, natural timber and MDF veneered door frames.

Ironmongery:

Range of offset top and bottom hinges, top and bottom pivots complete with floor spring (BTS75) or 100mm stainless steel Lift Off hinges that are complemented by a range of satin or polished stainless steel finished lever sets, pull handles and patch locks,

Drawings & Photographs:

Detailed junction drawings and a selection of installation photographs can be viewed on our web site **www.fusionpartitions.com**

Unit 6 : I O Centre : Salbrook Road Industrial Estate : Salfords : Surrey : RH1 5GJ
Tel 01293 220970 E-mail info@fusionpartitions.com