

Contempo Glide

Aluminium Framed Sliding Door

Single Glazed - Specification Overview



FRAMING DIMENSIONS:

30mm x 80mm aluminium perimeter frame.

ACOUSTICS PERFORMANCE:

12 mm Toughened safety glass with drop down threshold and full perimeter seals - Rw 34dB.

12.8mm Acoustic safety glass with drop down threshold and full perimeter seals - Rw 36dB.

INTEGRATION:

The door will fully integrated with all Fusion glazed partitioning systems and both the 75mm and 100mm plasterboard partition wall systems.

COLOUR FINISH:

Polyester powder coated in any BS4800 or RAL colours available to order.

A selection of anodised and other special finishes are also available to order.

MANIFESTATION:

To meet the requirements of Part M of the Building Regulations (*minimum 50mm dots @ 100mm centres*) or to clients specification using digital printed logos / graphics on film, screen printed or acid etched glass.

DOOR FRAME:

Aluminium framing components includes Deflection head (optional), Inner sliding head channel (SD2), Brush seal holder, Infill trims (X1 and X2) with vertical Front slam post (SD3), Rear slam post (SD.4) that incorporates a single glazing chair and a range of acoustic performance enhancing gaskets and brush seals,

IRONMONGERY:

The sliding door full adjustable fittings include Twin roller set, Track stop and Twin roller door floor guides that are complemented by a range of satin or polished stainless steel finished cranked pull handles.

DRAWINGS & PHOTOGRAPHS:

Detailed junction drawings and a selection of installation photographs can be viewed on our web site **www.fusionpartitions.com**

